





















LEGEND

## LIGHTING

- |   |  |
|---|--|
|        | 1200 LONG 45W LED LUMINAIRE WITH DRIVER - SYLVANIA 'SYLPROOF ECO' LED<br>1 = 24W FITTING   |
|        | AS ABOVE BUT WITH SELF CONTAINED EMERGENCY LIGHTING FROM ONE TUBE (NON-MAINTAINED)   |
|        | RECESSED 2x26W TROFFER WITH LAY-IN PRISMATIC DIFFUSER AND ELECTRONIC BALLAST   |
| W1<br> | WALL MOUNTED FORWARD DISTRIBUTION LIGHT<br>SYLVANIA 2x26W 'CASSINI' PLANAR*  |
| W2<br> | AS FOR TYPE W2 BUT WITH EMERGENCY LIGHTING PACK  |
| W3<br> | WALL MOUNTED UP/DOWN DISTRIBUTION LIGHT<br>LUMINAIRE 'INVERTO DIRECT-INDIRECT' 21W WITH INTEGRAL DRIVER - BLACK                      |
| W4<br> | WALL MOUNTED DOWN DISTRIBUTION LIGHT<br>'INVERTO DIRECT' IP65 16W WITH INTEGRAL DRIVER - BLACK                                       |
| W5<br> | 30W LED IP65 FLOODLIGHT - SYLVANIA 'IETA 2' WITH ADDED BEAM CONTROL LOUVERES ADJUSTED TO PREVENT SPILL LIGHT TO ADJACENT PROPERTIES. |
|        | IP65 LOW PROFILE SURFACE 155W LED LIGHT WITH INTEGRAL DRIVER. PIERLITE 'STELLAR LED' STSLED 155/74                                   |
| C1<br> | 3000K LED 21.8W RECESSED DOWNLIGHT. PIERLITE DOT 9400/9442-DL IP44   |
| C2<br> | 3000K LED RECESSED DOWNLIGHT AND DRIVER. SYLVANIA 'BIRRUNG 2' 60'  |
| C3<br> | AS FOR TYPE C1 BUT 18W   |
| EM<br> | 1.7W LED SELF CONTAINED, RECESSED NON MAINTAINED EMERGENCY FITTING.  |
|        | 1.2 WATT LED MAINTAINED EDGE/UT RECESSED EMERGENCY EXIT LIGHT<br>WALL OR CEILING SURFACE MOUNTED                                     |
|        | ULTRASONIC LIGHTING MOVEMENT SENSOR SWITCH   |
|        | AS ABOVE BUT 360°  |






SECURITY

- |   |                                      |
|---|--------------------------------------|
|  | ELECTRIC STRIKE                      |
|  | CARD KEY ACCESS POINT                |
|  | DOOR CONTROLLER EQUAL TO INNER RANGE |
|  | SECURITY CONTROL PANEL               |








POWER

- |    |   |
|----|---|
|    | SWITCHBOARD/DISTRIBUTION BOARD          |
|    | SINGLE GPO                              |
|    | DOUBLE GPO                              |
|    | LOCAL ISOLATOR                          |
|    | No. = No. Of PHASES                     |
| WP | EXTERNAL WEATHER PROOF GPO              |
|    | L = LOOKABLE                            |
|    | ELECTRIC HAND DRYER                     |
|    | INSTANTANEOUS HOT WATER UNIT BY PLUMBER |

AUDIO-VISUAL

-  MATV ANTENNA  
 SIGNAL AMPLIFIER  
 FT FLOOR TEE  
 MATV SOCKET OUTLET  
 MULTI TENANCY VIDEO-INTERCOM DOOR STATION AND POWER SUPPLY

SINGLE LINE DIAGRAM

- |   |   |
|---|---|
|    | THREE PHASE CIRCUIT   |
|    | SINGLE PHASE CIRCUIT  |
|    | CIRCUIT BREAKER   |
|    | 30mA ELCB   |
|    | LOAD BREAK ISOLATOR   |
|   | KEY LOCKABLE FACILITY   |
|  | KILOWATT HOUR METER, SUPPLIED AND<br>INSTALLED BY RETAILER      |
| <b>ABBREVIATIONS</b>  |   |
| U/S   | UNSWITCHED SECURITY LIGHT                                       |
| FR  | REFRIGERATOR  |
| OV  | OVEN  |
| <b>MOUNTING DETAILS</b>   |   |
| a   | =300mm AFFL   |
| b   | =600mm AFFL   |
| c   | =1000mm AFFL  |
| d   | =150mm ABOVE BENCHTOP   |
| e   | =WALL MOUNTED AT HEIGHT COORDINATED WITH PLUMBING<br>CONTRACTOR |

FOR APPROVAL

P2	FOR REVIEW - CHANGES AS CLOUDED		26.04.17	BF	
P1	FOR REVIEW		19.04.17	BF	
REVN	DESCRIPTION		DATE	CHK'D	
P.O. Box 200 Glen Osmond, S.A. 5064  Telephone 0412 388 922 Email sabect@vuzemail.com.au					
CLIENT					
					
PROJECT					
PROPOSED DEVELOPMENT at 147 MARION RD., RICHMOND					
DRAWING					
LEGEND AND SCHEMATICS POWER OUTLET					
ELECTRICAL SERVICES					
SCALE		DATE			
NTS		MARCH 2017			
DESIGNED BF		DRAWN MC		No. IN SET 1 of 4	
		DRAWING NUMBER		REVISION	
		A0733-1S-S01		P2	