

1.04 WINDOW SCHEDULE

Type		Comments
(A) Full Glass / Awning window	W10.1, W11.1, W12.1, W15.1, W5.1, W7.1, W6.1 W16.1, W13.6, W8.6, W4.2, W2.2, W2.3, W604, W605,	Non acoustic windows Obscure glass
(B) Full Glass / Sliding Window	W6.2, W11.2 W13.4, W14.4, W8.4, W12.3, W9.4 W10.3	Non acoustic windows Obscure glass
(C) Other Windows (Acoustic rated)	See Clause 1.5	Glazing as scheduled
(D) Glazed screens	DP5 / HR3 Privacy screens	Refer Metalwork section

1.05 ACOUSTIC WINDOW SCHEDULE

(A) Extent

Acoustic Apartment Windows (**denotes openable window to be fitted with Fire screens as specified)

SEC	Frame Type	Glazing	RwCTr	Extent of Door / Windows
1	Sliding window **	A	25	W13.5, W16.2, W15.2, W8.5, W12.4, W9.3, W10.4
1	Awning window	A	25	W5.2, W7.2,
1	Sliding window**	A	22	W16.3, W15.3, W12.2
1	Sliding window**	A	22	W10.2,
1	Sliding window**	A	28	W8.3
2	Sliding window**	A	28	W14.3
2	Sliding window **	C	31	W13.3
4	Awning window	C	34	W601, W602, W3.1
		A	31	W603, W4.1, W2.1
3	Awning window	A	31	W9.2, W9.1, W14.2, W14.1
3	Awning window	C	34	W8.1, W8.2, W13.2, W13.1

Glazing Legend (acoustic)			
A	-6mm thick safety glass	C	-10mm thick safety glass
B	-8mm thick safety glass	D	-12.5mm thick VLam Hush safety glass

Extent

All Apartments (Fixed / Sliding / awning / Windows / Doors)	- Performance glass as specified (Min SHGC 0.58 / U5.4)
Common Area (other areas)	-Clear toughened / laminated glass
Ground floor entry Doors / shopfront	-Clear toughened / laminated glass

Performance Glass Types

Viridian Glass	(SolTech Neutral) 6mm Laminated and toughened glass	SHGC 0.53 / U3.7
Viridian Glass	(Comfort plus Neutral 59) 8-10mm Laminated glass	SHGC 0.51 / U3.6

Seals

All openable windows and doors shall be fitted with the following acoustic seals or equal approved :

Frame	Seals / Other
50 series Awning window	Schlegel Q-Lon T-slot seals (or equal performance to suit frame)
950 series Sliding window	As specified for sliding doors (Refer Door specification)