

755PSMA4

smoke alarm, photoelectric, surf mount, 230V gen 4
battery backup



Main

Range	Firetek
Product brand	Clipsal
Product or component type	Smoke detector
Device application	Early detection of smouldering fires and open fires
Electronic sensor type	Photo-electric sensor
Colour	White (RAL 9003)
Quantity per set	Set of 1
Type of packing	Carton

Complementary

Supply	Mains
[Us] rated supply voltage	220...240 V AC
Backup type	Battery
Battery life	1 yr
Output voltage limits	Interconnection : 6.5...20 V
Type of alarms	Low battery at 6.9...7.5 V
Detection type	Smoke
Function available	Hush function Self-test of smoke detection Local alarm
Control type	Button for test/hush function
Number of devices	40 for wired alarm
Operating distance	50 m indoor use line of sight 140 m in free field
Response time	< 30 s
Noise level	85 dB at 3 m minimum
Time delay range	10 min for hush 10 h for do not disturb
Local signalling	Sound : alarm Sound : signal Visual : 1 LED (red) for warning and low battery Visual : 1 LED (green) for ON status
Type of installation	Indoor
Device mounting	Surface
Mounting support	Wall-mount Ceiling
Fixing mode	By screws
Diameter	140 mm
Height	47 mm

Environment

ambient air temperature for operation	0...45 °C
relative humidity	5...95 %
product certifications	RCM Activfire SAI
standards	AS/NZS 60065 AS/NZS 60950.1 ISO 8201 AS 3786: 2014

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1601 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold