

LEGENDS:

SMOKE ALARM - SELF CONTAINED,
INTERCONNECTED, HARD WIRED
IN ACCORDANCE WITH AS 3786

SUSPENDED PLASTERBOARD
CEILING HEIGHT AT 2100mm ABOVE AFFL

SUSPENDED PLASTERBOARD
CEILING HEIGHT AT 2700mm ABOVE AFFL

SUSPENDED PLASTERBOARD
CEILING HEIGHT AT 3000mm ABOVE AFFL

SUSPENDED PLASTERBOARD
CEILING HEIGHT AT 3200mm ABOVE AFFL

CH 3000

SSH 3000

CON

CEILING HEIGHT

SLAB SOFFIT HEIGHT

CEILING FINISHES CODE

CEILING GENERAL NOTES

- ALL GRID IS JUST A GENERAL
REFERENCE.
REFER TO GENERAL ARRANGEMENT
PLANS FOR GRIDS AND UNIT TYPE
LOCATION.

- ALL CEILINGS TO BE 13mm
PLASTERBOARD EXCEPT ABOVE WET
AREAS WHERE MOISTURE RESISTANT
PLASTERBOARD IS TO BE USED.

- CARPORCH TO HAVE MIN. 3000mm
CLEAR HEADROOM GENERALLY UNLESS
NOTED OTHERWISE

- ACOUSTIC INSULATION IN CEILINGS
REFER TO ACOUSTIC REPORT FOR
DETAILS.

- THERMAL INSULATION IN CEILINGS REFER
TO BASIX REPORT AND SECTION J JV3
REPORT FOR DETAILS.

- ALL CEILINGS TO HAVE THERMAL
INSULATION + PLASTERBOARD
WHERE EXPOSED TO ROOF ABOVE.

- COORDINATE CEILING INSTALLATION
WITH WALL INSTALLATION AND ALL
BUILDING SERVICES TRADES.

- PROVIDE 300mm DIAMETER CUT OUT
TO INSULATION ABOVE LIGHT FIXTURES.

- PROVIDE ACOUSTIC INSULATION UNDER
LAGGED PIPEWORK ABOVE HABITABLE
AREA.

- REFER TO EXTERNAL FINISHES SCHEDULE
FINISHES AND SPECIFICATION DETAIL.

- ELECTRICAL LAYOUT TO CLIENT'S AND
BUILDER'S SELECTION.

- ALL STEEL STRUCTURE REFER TO ENG'S
DRAWINGS FOR DETAILS & READ IN
CONJUNCTION WITH SERVICES
DOCUMENTATION FOR HEADROOM
COMPLIANCE.

ELECTRICAL LEGEND

SINGLE GPO

DOUBLE GPO

TV POINT

EXHAUST FAN

11W LED DOWN LIGHT

WALL MOUNT LIGHT

TELEPHONE POINT

DATA

MOTION SENSOR

LIGHT POINT

UNDER BENCH

ABOVE BENCH

WATER PROOF

FLOOR RECESSED GPO

FEATURE LIGHTING

NOTE:

SMOKE DETECTOR HARDWIRED TO CONSUMER MAINS WITH 9V
BATTERY BACKUP INSTALLED IN ACCORDANCE WITH AS 3786 - 1993

ALL REQUIRED SMOKE ALARMS SHALL BE INTER-CONNECTED

ALL LIGHT SWITCHING TO BE RESOLVED ON SITE WITH
PROPRIETOR

ALL BEDROOM LIGHT SWITCHING WITH DIMMER

ALLOW 4 OFF EXTERNAL POWERPOINT FOR PUMP/SERVICES

FLOOR RECESSED GPO LOCATION TO BE CONFIRM ONSITE

Ground floor plan of Type D. The plan shows a large open area with a 'VOID STAIR' and a 'TILT UP PANEL DOOR'. Electrical symbols include smoke alarms (S1), ceiling heights (CH 2100, CH 2700, CH 3000), and various lighting points (AB, DP). A feature lighting symbol is also present.

1

TYPE D - GROUND FLOOR

First floor plan of Type D. The plan shows a large open area with a 'VOID STAIR' and a 'TILT UP PANEL DOOR'. Electrical symbols include ceiling heights (CH 2700, CH 3000), various lighting points (AB, DP), and a feature lighting symbol.

2

TYPE D - FIRST FLOOR

IMPORTANT NOTES: Do not scale from drawings. All dimensions to be checked on site before commencement of work. All discrepancies to be brought to the attention of the Designer. Larger scale drawings and written dimensions take preference. This drawing is copyright and the property of the author, and must not be retained, copied or used without the express authority of NIC DESIGN STUDIO PTY LTD	REVISION	DATE	DESCRIPTION	BY	<div><div>n c design</div><div>nic</div></div>	CLIENT HUIDA UNLEY PARK NO.1		DRAWING TITLE RCP - TYPE D GROUND & FIRST FLOORS			
	1	26/10/2018	PRELIMINARY	AR/KR		PROJECT UNLEY ROAD 392-394 UNLEY ROAD, UNLEY PARK 5061		SCALE 1 : 50 @A1 1 : 100 @A3	DATE OCT 2018	DRAWN AR/KR	CHECKED NW
	2	14/02/2019	ISSUE FOR INFORMATION	KR				JOB 19002	DRAWING A2.127		REVISION 2