



**NOTE:**  
ALL SEWER AND TRADE WASTE PIPEWORK SHALL BE INSTALLED AT THE FOLLOWING MINIMUM GRADES UNLESS OTHERWISE STATED:  
• Ø40-Ø75: 2.50% MINIMUM  
• Ø110: 1.65% MINIMUM  
• Ø160: 1.00% MINIMUM  
ALL VENT PIPEWORK SHALL BE INSTALLED AT 1.25% MINIMUM GRADE UNLESS OTHERWISE STATED.

A	CONSTRUCTION ISSUE	14.02.2020	KR
REV N	DESCRIPTION	DATE	CHK'D

© Copyright Lucid Consulting Australia 13/02/2020 4:41:24 PM

FOR CONSTRUCTION



Level 3/169, Pirie St Adelaide SA 5000  
Phone: (08) 8407 9700  
Email: [adelaide@lucidconsulting.com.au](mailto:adelaide@lucidconsulting.com.au)

PROJECT  
HYDE PARK PLACE  
248 UNLEY ROAD, HYDE PARK  
HYDRAULIC SERVICES

DRAWING  
SANITARY DRAINAGE AND TRADE WASTE DRAINAGE  
SCHEMATIC

NOT FOR CONSTRUCTION PURPOSES UNLESS STAMPED FOR CONSTRUCTION. VERIFY DIMENSIONS AND LEVELS ON SITE BEFORE SETTING OUT. DO NOT SCALE. REFER TO FIGURED DIMENSIONS - IN mm UNLESS OTHERWISE STATED.			
Scale NTS	Design: JZ Drawn: JZ Review: KR	No. in Set 22 of 25	Date JAN 2020
Orig. Size A1	Drawing no. LCE14462-H300	Revision A	