



LEGEND

15.55	SEWER GRADE PVC STORMWATER PIPE SIZE AS NOTED (S/S DENOTES SEALED SYSTEM)
AG	AG DRAIN TO BACK OF RETAINING WALL
S450-C	450 SQUARE GRATED SUMP WITH CLASS C GRATE FITTED WITH PROPRIETARY TRASH RACK TO MANUF'S DETAILS
S200/300	200/300 SQUARE GRATED SUMP WITH CLASS B GRATE
DP	DOWNPIPE ALL DOWNPIPES FOR SEALED SYSTEM ARE TO BE PVC
SIP	SITE INSPECTION POINT
GD	100 WIDE ACO GRATED DRAIN (OR APPROVED EQUIVALENT) WITH CLASS B GRATE
GD2	200 WIDE ACO GRATED DRAIN (OR APPROVED EQUIVALENT) WITH CLASS D GRATE
15.55	DESIGN LEVEL P - PAVING C - CONCRETE G - GROUND

15.55	CONTOUR LINE SIZE AS NOTED
←	DIRECTION OF SURFACE FALL
---	GRADE LINE
EC	CONCEALED CONCRETE EDGE RESTRAINT
RW	PROPRIETARY CONCRETE SLEEPER RETAINING WALL LESS THAN 1.0m IN HEIGHT
CU	CONCRETE UPSTAND
RWT	1.0 KL SLIMLINE RAINWATER TANK TO MANUF'S DETAILS PLUMBED BACK INTO BUILDING AS PER AS 3500
DT	10.5 KL DETENTION TANK STRICTLY IN ACCORDANCE WITH MANUF'S DETAILS PROVIDE INSPECTION OPENINGS, BREATHER VALVES, ETC. STRICTLY IN ACCORDANCE WITH MANUF'S DETAILS
PRM	PUMP RISING MAIN TO PUMP MANUFACTURERS DETAILS

80mm THICK INTERLOCKING CLAY/CONCRETE PAVER (UNPAVE OR SIMILAR) ON 30mm MAX COMPACTED BEDDING SAND ON 100 THICK FINE CRUSHED ROCK (PM1/200G / PM1/400G) ON 150 THICK COMPACTED QUARRY RUBBLE (PM2/200G) (WITHIN BASEMENT EXTENT PAVEMENT ON CONCRETE SLAB REFER STRUCTURAL DRAWINGS)
60mm THICK CONCRETE PAVER TO ARCHITECT'S SELECTION ON 30mm MAX COMPACTED BEDDING SAND ON 100 THICK FINE CRUSHED ROCK (PM1/200G / PM1/400G) (WITHIN BASEMENT EXTENT PAVEMENT ON CONCRETE SLAB REFER STRUCTURAL DRAWINGS)
FOOTPATH WORKS AS SEPERABLE PORTION IN ACCORDANCE WITH COUNCIL'S SPECIFICATION
TILES TO ARCHITECT'S SELECTION ON CONCRETE SLAB REFER STRUCTURAL DRAWINGS

NOTE:
REFER TO ARCHITECT'S DRAWINGS FOR ALL SETOUT
DIMENSIONS
ALL LEVELS SHALL BE CONFIRMED ON SITE PRIOR TO
CONSTRUCTION. SHOULD ANY DISCREPANCY OCCUR THE
CONTRACTOR SHALL CONTACT THIS OFFICE IMMEDIATELY
FOR FURTHER INSTRUCTION.

CONTRACTORS NOTES:
COVER LEVELS GIVEN FOR PITS ARE NOMINAL ONLY.
COVER LEVELS SHALL MATCH FINISHED PAVING LEVELS.
THE CONTRACTOR IS RESPONSIBLE FOR CHECKING
LOCATION OF ALL UNDERGROUND SERVICES PRIOR TO
COMMENCING ANY EXCAVATION WORK. ANY DAMAGE
CAUSED TO ANY SERVICES SHALL BE REPORTED
IMMEDIATELY TO THE SUPERINTENDANT & SHALL BE
REPAIRED BY THE APPROPRIATE AUTHORITIES. ALL
COSTS ASSOCIATED WITH REPAIRS SHALL BE AT THE
CONTRACTOR'S EXPENSE. PHONE 'DIAL BEFORE YOU DIG'
(1100) FOR ASSISTANCE.

02.07.2019	ISSUED FOR TENDER	T
28.03.2019	ISSUED FOR APPROVAL	D
12.03.2019	PRELIMINARY ISSUE	C
01.03.2019	PRELIMINARY ISSUE	B
06.02.2019	ISSUED FOR INFORMATION	A
Date	Revision	Issue

Designed	SR	Drawn	SR
Approved		Date	JAN 19
CIVIL		Sheet	2 of 3

Project
**PROPOSED DEVELOPMENT
248 UNLEY ROAD
HYDE PARK SA**

Client CITIFY & BFC PTY LTD	N
Drawing Title GROUND FLOOR LEVELS & DRAINAGE LAYOUT	Scale 1:100
Drawing Number 20492-C02	Issue T